

**WATER PUMPING SETS**

**Model :: LPG based pumpset WBL 30**



<b>Engine Parameters</b>	
Type	GX 160
Displacement (c.c.)	163
Rated Output (HP)	4.3
Fuel Starting	LPG
Running	LPG

  

<b>Pump Parameters</b>	
Size (mm)	80 x 80
Max. Head (Metres)	26
Max. Discharged (Ltr/Minute)	900
Rated Speed (RPM)	3400
Weight (Kg.)	29

  

<b>FEATURES</b>	
Oil Alert	Yes
Priming	Self
Material of Pump	Aluminium Alloy
Multi Crop Lever	Yes
Carrying Arrangement	Tubular Frame

**WATER PUMPING SETS**

**Model :: WBK15**



<b>Pump Parameters</b>	
Type	*
Inlet Diameter	38mm (1.5")
Outlet Diameter	38mm (1.5")
Total Head (Metre)	38
Suction Head (Metre)	7
Maximum Discharge (lit./min.)	200
Self-Priming time for five metre Suction Lift	120 Sec.
<b>Engine Parameters</b>	
Type	**
<b>Dimensions Parameters</b>	
LxWxH (mm)	384x297x357
Dry Weight (kg)	14
* Centrifugal, Self-Priming.	
** 4 Stroke, Forced Air Cooled, Horizontal Shaft.	

**WATER PUMPING SETS**

**Model :: WBK30**



<b>Pump Parameters</b>	
Type	*
Inlet Diameter	80mm (3")
Outlet Diameter	80mm (3")
Total Head (Metre)	28
Suction Head (Metre)	8
Max. Capacity (lit./min.)	1000
Self-Priming time for 5 metre Suction Lift	150 Sec.

<b>Engine Parameters</b>	
Type	**
Maximum Horse Power	4 HP/3600~4000 RPM
Fuel Tank Capacity - Gesoline (Itrs.)	0.40
Fuel Tank Capacity - Kerosene (Itrs.)	3.90

<b>Dimensions Parameters</b>	
LxWxH (mm)	600x490x485
Dry Weight (kg)	28

\* Centrifugal, Self-Priming, handle Carry.  
\*\* 4 Stroke, Air Cooled, Single Cylinder, Horizontal Shaft.

**WATER PUMPING SETS**

**Model :: WBK30FF**

**Pump Parameters**

Type	*
Inlet Diameter	80mm (3")
Outlet Diameter	80mm (3")
Total Head (Metre)	28
Suction Head (Metre)	8
Max. Capacity (lit./min.)	1000
Self-Priming time for 5 metre Suction Lift	150 Sec.

**Engine Parameters**

Type	**
Maximum Horse Power	4 HP/3600 RPM
Fuel Tank Capacity - Gesoline (Itrs.)	0.40
Fuel Tank Capacity - Kerosene (Itrs.)	3.90

**Dimensions Parameters**

LxWxH (mm)	623x490x498
Dry Weight (kg)	32

\* Centrifugal, Self-Priming, Full Frame.  
\*\* 4 Stroke, Air Cooled, Single Cylinder, Horizontal Shaft.

**WATER PUMPING SETS**

**Model :: WPK20**



<b>Pump Parameters</b>	
Type	*
Inlet Diameter	50mm (2")
Outlet Diameter	50mm (2")
Total Head (Metre)	30
Suction Head (Metre)	8
Max. Capacity (lit./min.)	600
Self-Priming time for five metre Suction lift	90Sec.
<b>Engine Parameters</b>	
Type	**
<b>Dimensions Parameters</b>	
LxWxH (mm)	515x440x487
Dry Weight (kg)	26.5
* Centrifugal, self-Priming, Handle carry.	
** 4 Stroke, Air Cooled, Single Cylinder, Horizontal Shaft.	

**WATER PUMPING SETS**

**Model :: WSK2020**

**Pump Parameters**

Type	*
Inlet Diameter	50mm (2")
Outlet Diameter	50mm (2")
Total Head (Metre)	30
Suction Head (Metre)	8
Max. Capacity (lit./min.)	600
Self-Priming time for five metre Suction lift	90Sec.

**Engine Parameters**

Type	**
------	----

**Dimensions Parameters**

LxWxH (mm)	540x440x476
Dry Weight (kg)	29.5

\* Centrifugal, self-Priming, Handle carry.  
\*\* 4 Stroke, Air Cooled, Single Cylinder, Horizontal Shaft.



**Head Office** Caple Traders , 6, 7, 8 Kedia Chambers, Opp. Old Police Station, Near New Era Theatre, S.V. Road, Malad (W), Mumbai – 400064.  
Tel: 022-28825542, 28894090, 28898531 | Fax: 022-28899725 | E-mail: [web@caple.in](mailto:web@caple.in) | Website: [www.caple.in](http://www.caple.in)

**Demo Centre** Caple Traders, Navdurga, Shah Arcade Building No. 8, Near Rani Sati Flyover, W.E. Highway, Malad (E), Mumbai - 400 097.  
Tel: +91-22-28803584, 28803586 | Fax: +91-22-28441071 | E-mail: [web@caple.in](mailto:web@caple.in) | Website: [www.caple.in](http://www.caple.in)

## Query Sheet

Company Name & Address -

Delivery Name & Address -

Contact Person -

Designation -

Mobile No -

Fax No -

Mail Id -

Item -

Model No (If Known) -

Capacity Size -

Application -

Expected Delivery Time -

Notes -

E-mail: [contact@caple.in](mailto:contact@caple.in)    Mobile: (91) 99200 71716

