

TILTING ARBOUR SPINDLE MOULDERS



Model : J-504 (T)



Dovetailed groove for easy sliding. Also equipped with a convenient wood clamping facility



Arch moulding fixture and ball bearing roller collar

Auto Feeder :

It can be fixed on this Max-moulder and can be bought any time separately.

Models :

AF-34 : 3 Roller, 4 speed, 1 HP 3Ø motor
AF-32 : 3 Roller, 2 speed, ¼ HP 3Ø motor



SPINDLE MOULDER	MAX	MASTER	MASTER
Model No.	J-504 (T)	J-504 (H)	J-504
	mm / inch	mm / inch	mm / inch
Work table size	835 x 760 33" x 30"	835 x 835 33" x 33"	760 x 760 30" x 30"
Spindle diameter	31.75 / 1¼"	31.75 / 1¼"	31.75 / 1¼"
UP / Down movement of spindle	100 / 4"	125 / 5"	125 / 5"
Arbour tilt - degree	45°	-	-
Spindle speed (RPM)	6000	6000	5000
Power required - HP / RPM	3 / 2800	3 / 2800	3 / 2800

STANDARD ACCESSORIES :- Moulding block one no. each of 1", 2" & 3" width, motor pulley, motor fixing plate, washers set, toolkit & m/c manual.
• Arch moulding fixture in model no : J-504 (T) & J-504 (H)
• Bearing guide & mitre gauge with wood clamping facility in model no : J-504 (T)
• Mitre gauge in model no. : J-504

SPINDLE MOULDERS



Arch moulding fixture

Model : J-504 (H)

Basic Spindle Moulder



Special facility for Routing work



Model : J-404

Note : The speed of 9000 RPM is advisable for routing work only

POPULAR - BASIC SPINDLE MOULDER	
Model No.	J-404
	mm / inch
Work table size	610 x 610 24" x 24"
Spindle diameter	25.4 / 1"
UP / Down movement of spindle	100 / 4"
Spindle speed (RPM)	6000 / 9000
Power required - HP / RPM	2 / 2800

STANDARD ACCESSORIES :- Routing rip fence, Moulding block 1 no. each of 1" & 2" width, motor pulley, motor fixing plate, washers set & V-belt guard, Collet-12 mm hole with 8 mm hole sleeve, Sample router cutter-1 no. toolkit & m/c manual



Model : J-504