



## FEIN Dustex 35 LX

### Wet / dry dust extractor

Powerful, professional wet/dry dust extractor of dust class L for attachment of various case systems including extensive accessories.

Product number: 9 20 29 060 00 0

#### **Details**

- > Tool cases of various systems can be simply positioned on the extraction head and secured.
- > Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- > Reliable suction of different types of dirt from liquids to fine dusts.
- > Approval for dust class L.
- > With PES flat fold filter and electronic shut-off for outstanding wet extraction performance.

- > Auto start socket with switch-on delay to avoid power surges.
- > Infinitely variable suction force regulation on the extractor.
- > The 7.5 m mains cable and 4 m hose provide a large working radius.
- Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0.



#### Price includes

- 1 push bar
- 1 premium fleece filter bag
- 1 tool collar with suction force regulation
- 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

- 1 PES flat fold filter
- 1x 4 m suction hose, diameter 35 mm
- 1 stepped collar

#### Product feature

- Automatic start/stop
- Antistatic preparation
- Case storage

- Soft start
- Anti-static function
- Dust class

#### Technical data

#### TECHNICAL DATA

# VIBRATION AND SOUND EMISSION VALUES

| Maximum power input      | 1,380 W     | Sound pressure level LpA<br>Uncertainty of measured value<br>KpA |
|--------------------------|-------------|--|
| Air flow                 | 4,320 l/min |  |
| Max. vacuum              | 254 hPa     | Sound power level LWA Uncertainty of measured value KWA          |
| Tank volume              | 351         | Vibration value 1 αhv 3-<br>way<br>Vibration value 2 αhv 3-way   |
| Cable with plug          | 7.5 m       |  |
| Sound pressure level     | 67 dB       |  |
| Weight according to EPTA | 13.50 kg    |  |
|                          |             |  |

| Uncertainty of measured value KpA                             | 3 dB                  |
|---|-----------------------|
| Sound power level LWA<br>Uncertainty of measured value<br>KWA | 81,0 dB<br>3 dB       |
| Vibration value 1 αhv 3-<br>way                               | <2,5 m/s <sup>2</sup> |
| Vibration value 2 αhv 3-way                                   | 1,5 m/s <sup>2</sup>  |

67,0 dB



# Application examples

