



BLK 2.0 E

Nibbler up to 2 mm

Compact nibbler with unlimited curve precision for corners and edges.

Product number: 7 232 40 60 00 0

Details

- > High curve precision due to special cutting head geometry. Nibbler can turn on the spot.
- > Especially well-suited for cutting edged sheet metals with a minimum bend radius of 3 mm.
- Cutting direction setting can be changed in 45° steps up to 360° using tool-free pivoting cutting head
- > QuickIN clamping system.Optimal ergonomics.

- Motor with outstanding performance and stability.
- > Ideal for cut-outs.
- > Optimally suited for template cuts.
- > Chip protection mesh on vent slots.
- > 5 metre cable.
- > Stainless steel up to 1.0 mm.

Price includes

1 die (3 13 09 040 00 2)

1 punch (6 36 02 051 00 9)

Product feature

Cutting direction


QuickIN



Application

Curve cuts

Cut-outs



★ suitable

★★ well suitable

Technical data

TECHNICAL DATA

Input	350 W
Output	210 W
Strokes	500 - 1,000 rpm
Cutting speed	1 m/min
Steel up to 400 N/mm ²	2 mm
Steel up to 600 N/mm²	1.5 mm
Steel up to 800 N/mm²	1 mm
Non-ferrous metals up to 250 N/mm ²	2.5 mm
Cutting width	8 mm
Immersion Ø with die	18 mm
Rad. of smallest curve (inside/outside)	4 / 0 mm
Cable with plug	5 m
Weight according to EPTA	1.80 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	80 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	91 dB 3 dB
Sound peak value	91 dB
LpCpeak Uncertainty of measured value KpCpeak	3 dB
Vibration value 1 αhv 3-	7,3 m/s ²
Way Uncertainty of measured value $\mbox{K}\alpha$	1,5 m/s²



Application examples

