



BLK 5.0

Nibbler up to 5 mm

Powerful nibbler for heavy dismantling and cutting applications.

Product number: 7 232 31 00 23 9

Details

- Powerful 1 200 W motor for outstanding performance while maintaining excellent ergonomics.
- > Cuts over 90° edges, for example on guard rails or tanks.
- > Cutting direction can be adjusted in 90° steps without the need for tools.
 - Optimum power-to-weight ratio.

- Long tool life of punch and die.
- > Chip protection mesh on vent slots.
- > Handle can be rotated 180°.
- > 5 metre cable.
- > Stainless steel up to 2.5 mm.
- > Wide range of accessories.

Price includes

- 1 die (3 13 09 107 00 0)
- 1 punch (3 13 09 110 00 4)

1 additional handle

Product feature

Cutting direction



★ suitable

★ ★ well suitable

Application

Curve cuts

Technical data

TECHNICAL DATA

VIBRATION AND SOUND EMISSION VALUES

 \star

Input	1,200 W	Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Output	750 W		
Strokes	750 rpm	Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Cutting speed	1.3 m/min	Sound peak value	100 dB
Steel up to 400 N/mm ²	5 mm	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Steel up to 600 N/mm²	3.3 mm	Vibration value 1 αhv 3-	10 m/s²
Steel up to 800 N/mm ²	2.5 mm	Way Uncertainty of measured value Kα	1,5 m/s ²
Non-ferrous metals up to 250 N/mm²	7 mm	i cu	
Cutting width	8 mm		
Immersion Ø with die	43 mm		
Rad. of smallest curve (inside/outside)	86 / 94 mm		
Cable with plug	5 m		
Weight according to	3.80 kg		

Weight according to EPTA



Application examples

