



MSfo 870-1d 300 Hz 200 V

HF angle grinder up to Ø 180 mm

The most powerful FEIN HF angle grinder for extreme grinding work.

Product number: 7 820 77 00 26 0

Details

- > Metal motor and gearbox housing for maximum load capacity in industrial continuous use.
- Fully encapsulated motor, 100 % dust protection with surface cooling for maximum stability and service life even under extreme conditions of use.
- > Low-wear and low-maintenance.
- > Maximum reliability and outstanding service life.
- > High effective output.
- > Great speed consistency.

Price includes

- 1 wheel guard
- 1 set of keys



- 1 pair of flanges
- 1 anti-vibration handle

Product feature

Fully encapsulated motor



Application

Roughing-down

Deburring

Dividing

Technical data TECHNICAL DATA

★ suitable★ ★ well suitable

VIBRATION AND SOUND EMISSION VALUES

Input	3,700 W	Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Output	2,800 W		
Frequency	300 Hz	Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Voltage/type of current	200 V/3~	Sound peak value LpCpeak Uncertainty of measured value KpCpeak Vibration value 1 αhv 3- way Uncertainty of measured value	100 dB
Speed, no load	8,600 rpm		3 dB
Grinding disc Ø	180 mm		4,7 m/s²
Elast. Backing pad Ø	180 mm		1,5 m/s ²
Flange	M 14	Κα	
Cable	5 m		
Weight according to EPTA	8.20 kg		



Application examples









