

RADIAL ARM SAWS

formula sr 650



Technical data		SR 650
Blade diameter	mm	350 ÷ 400
Blade tilting		-45° ÷ +45°
Max. cutting depth with blade at 90°/45°	mm	120/83*
Cross cut capacity	mm	640 x 20
Three-phase motor		3kW (4hp) 50Hz 3kW (4hp) 60Hz

STANDARD EQUIPMENTS

- Cast-iron arm, column, pedestal and carriage
- Interchangeable sliding ways
- Carriage with 8 adjustable bearings
- Column protection cover

Production Code: SR 650

109999	Security execution	N. 1
RF0641	formula sr 650 Radial arm saw complete with: - start/stop pushbutton (ON-OFF)	N. 1
930772	Voltage 400 EU	N. 1
931205	Frequency 50 hz	N. 1
580428	Rollers table, 1 meter length, on the blade left side (each) N.B. - "Aluminium fence on the table" option is compulsory	N.1
580401	Roller table, 1 meter length, on the blade right side (each) N.B. "Aluminium fence on the table" option is compulsory.	N.1
580429	Aluminium fence on wooden table in place of the wooden fence supplied as standard	N. 1
580430	Manual side stop (each) N.B. "Aluminium fence on the table" option is compulsory.	N. 1
580431	Blade guard for blade, 400 mm diameter	N. 1
580433	TCT blade, 400 mm diameter	N.1
080679	Wooden crate packing (dimensions: 1260 x 1140 x 890 mm - gross weight: 259 kg)	
109991	Machine language: ENGLISH	N. 1