

# WOOD TURNING LATHE

## minimax t 124



### MAIN FEATURES



**TRANSPARENT GUARD FOR THE TOTAL OPERATOR SAFETY**



**VERSATILE FOR ANY ALL USE NECESSITY DUE TO THE FULL RANGE OF DEVICES**

Technical features		t 124
- distance between centres	[mm]	1150
- centres height	[mm]	200
- 4 chuck speeds (at 50 Hz)	[rpm]	570/1000/1850/2500
- tape drive with morse taper	[n.]	2
- ball bearing centre with morse taper	[n.]	2
- faceplate diameter	[mm]	130
- three-phase motor S6		1,5kW (2hp) 50Hz - 1,8kW (2,5hp) 60Hz
<u>Machine equipped with copying device (option):</u>		
- max. working length	[mm]	1120
- max. diameter	[mm]	200
<u>and equipped with mobile rest (option):</u>		
- max. working length	[mm]	1070
- max. diameter	[mm]	80

#### STANDARD EQUIPEMENT

- Extra sturdy frame
- Tool rest

**Codice produttivo: T/124**

<b>104000</b>	<b>Ce norms</b>	<b>N. 1</b>
<b>R90511</b>	<b>minimax t 124 with copying device - CE version</b> Wood turning lathe with devices in conformity with european safety regulations and complete with: - copying device - floor stand and tool tray	<b>N. 1</b>
<b>930772</b>	<b>Voltage 400 EU</b>	<b>N. 1</b>
<b>931205</b>	<b>Frequency 50 hz</b>	<b>N. 1</b>
<b>523870</b>	<b>Chuck, 120 mm diameter</b> with attachment M33 x 3,5 mm and protection	<b>N. 1</b>
<b>451096</b>	<b>Cup chuck diam. 40 mm</b>	<b>N. 1</b>
<b>451097</b>	<b>Screw chuck diam. 70 mm</b>	<b>N. 1</b>
<b>083560</b>	<b>Triple wall packing for machine with floor stand</b>	<b>N. 1</b>
<b>109991</b>	<b>Machine language: ENGLISH</b>	<b>N. 1</b>