

SYSTEM1 : For Nanxing Edge Banding machine NB7X

With special portable dust collector

SUPPLY, INSTALLATION AND COMMISSIONING DUST EXTRACTION SYSTEM FOR NANXING EDGE BANDING MACHINE NB7X FOR MINIMUM CAPACITY OF 7000-8000 CMH COMPRISES OF:

1.	PORTABLE DUST COLLECTOR of our model AXC-PDC-10HP-DS-RD+DUCT for minimum capacity of 7000-8000 CMH comprises of directly driven Centrifugal Fan of our type AXC-HMS-26-Arr" A" driven by 10hp/2p Motor <ul style="list-style-type: none">• Top 14no high efficiency Polyester Needle felt Non-woven anti-static Filter bags with Teflon coating inside-12M².• Bottom 2no collection bag to collect .35 m³• L&T make DOL starter and• Suction adaptor.• Total assembly mounted on a rigid movable trolley with wheels having jack.	1 No
2.	GI fabricated and powder coated special Aerodynamic ducts on top of machine with duct supports, wire rope support for hanging ducts from roof with Clamps, Turn buckle for tensioning.	1 Set
3.	PU & PVC Flexible Hose and Clamps. PU-Φ350 x 1000Long. PVC-Φ125 x 2500 Long, Φ15" clamps= 2 nos.Φ6" clamps= 8 nos.	1 Set
4.	Wooden Pallet	1 No



