

**SYSTEM1 : For Edge banding Machine NB7CJ**

With special portable dust collector

**SUPPLY, INSTALLATION AND COMMISSIONING DUST EXTRACTION SYSTEM FOR EDGE BANDING MACHINE NANXING MAKE NB7CJ FOR MINIMUM CAPACITY OF 7000-8000 CMH COMPRISES OF:**

1.	<b>PORTABLE DUST COLLECTOR</b> of our model <b>AXC-PDC-10HP-DS-RB</b> for minimum capacity of <b>7000-8000 CMH</b> comprises of directly driven Centrifugal Fan of our type <b>AXC-HMS-26-Arr" A"</b> driven by <b>10hp/2p Motor</b> <ul style="list-style-type: none"><li>• <b>Top 14no</b> high efficiency Polyester Needle felt Non-woven <b>anti-static</b> Filter bags with <b>Teflon coating</b> inside-<b>12M<sup>2</sup></b>.</li><li>• <b>Bottom 2no</b> collection bag to collect <b>.35 m<sup>3</sup></b></li><li>• <b>L&amp;T</b> make <b>DOL starter</b> and</li><li>• <b>Suction adaptor.</b></li><li>• Total assembly mounted on a rigid movable <b>trolley with wheels having jack.</b></li></ul>	<b>1 No</b>
2.	<b>GI</b> fabricated and powder coated <b>special Aerodynamic ducts</b> on top of machine with duct supports, wire rope support for hanging ducts from roof with Clamps, Turn buckle for tensioning.	<b>1 Set</b>
3.	<b>PU &amp; PVC Flexible Hose and Clamps.</b> PU-Φ350 x 1000Long. PVC-Φ125 x 2500 Long, Φ15" clamps= 2 nos.Φ6" clamps= 8 nos.	<b>1 Set</b>
4.	<b>Wooden Pallet</b>	<b>1 No</b>

