

SYSTEM 1: For CNC Drilling Machine NCG2812LE / DC-PDC-NCG2812LE

SUPPLY, INSTALLATION AND COMMISSIONING OF INDIVIDUAL DUST EXTRACTION SYSTEM FOR CAPACITY OF 7000–8000 CMH FOR CNC DRILLING MACHINE NCG2812LE



No.	Description	Qty.
1	<p>Portable Dust Collector model AXC-PDC-10HP-DS for minimum capacity of 7000–8000 CMH, comprising directly driven centrifugal fan type AXC-HMS-26-Arr“A” driven by 10hp/2p motor.</p> <p>Applicable features:</p> <ul style="list-style-type: none"> • Top 14 no. high-efficiency polyester needle-felt non-woven anti-static filter bags with Teflon coating inside. • Bottom 2 no. collection bags to collect 0.35 m³. • DOL starter. • PDC suction adaptor and machine adaptor. • Rigid movable trolley with wheels and jack. 	1 No
2	GI fabricated and powder-coated special aerodynamic ducts on top of machine with duct supports, wire-rope support for hanging ducts from roof, clamps and turn buckle for tensioning.	1 Set
3	PVC flexible hose and clamps.	1 Set
4	Wooden crate.	1 Set

Supply Components & Visual Reference

Item	Structured Details
Application	<ul style="list-style-type: none"> Of individual dust extraction system for capacity of 7000–8000 cmh for cnc drilling machine ncg2812le.
Dust collector	<ul style="list-style-type: none"> Portable dust collector with direct-driven centrifugal fan and integrated bag-filter/collection arrangement.
Ducting	<ul style="list-style-type: none"> GI fabricated, powder-coated aerodynamic ducting with supports and clamps as applicable.
Accessories	<ul style="list-style-type: none"> Flexible hose, clamps, adaptors, starter and packing components as listed in the supply table.

Images

Visual Reference 1



Visual Reference 2



Visual Reference 3

