

SYSTEM 1: For CNC Drilling Machine NB612FT2 / DC-PDC-NB612FT2

SUPPLY OF PORTABLE DUST COLLECTOR FOR MINIMUM CAPACITY OF 6000–6500 CMH FOR CNC DRILLING NB612FT2



| No. | Description | Qty. |
|-----|--|--------------|
| 1 | <p>Portable Dust Collector model AXC-PDC-7.5HP-DS for minimum capacity of 6000–6500 CMH, comprising directly driven centrifugal fan type AXC-HMS-26-Arr“A” driven by 10hp/2p motor.</p> <p>Applicable features:</p> <ul style="list-style-type: none"> • Top 14 no. high-efficiency polyester needle-felt non-woven anti-static filter bags with Teflon coating inside. • Bottom 2 no. collection bags to collect 0.35 m³. • DOL starter. • PDC suction adaptor and machine adaptor. • Rigid movable trolley with wheels and jack. | 1 Set |
| 2 | GI fabricated and powder-coated special aerodynamic ducts on top of machine with duct supports, wire-rope support for hanging ducts from roof, clamps and turn buckle for tensioning. | 1 Set |
| 3 | PVC flexible hose and clamps. | 1 Set |
| 4 | PU flexible hose and clamps, Φ200. | 1 Set |
| 5 | Wooden crate. | 1 Set |

Supply Components & Visual Reference

| Item | Structured Details |
|-----------------------|--|
| Application | <ul style="list-style-type: none"> • Portable dust collector for minimum capacity of 6000–6500 cmh for cnc drilling nb612ft2. |
| Dust collector | <ul style="list-style-type: none"> • Portable dust collector with direct-driven centrifugal fan and integrated bag-filter/collection arrangement. |
| Ducting | <ul style="list-style-type: none"> • GI fabricated, powder-coated aerodynamic ducting with supports and clamps as applicable. |
| Accessories | <ul style="list-style-type: none"> • Flexible hose, clamps, adaptors, starter and packing components as listed in the supply table. |

Images

Visual Reference 1



Visual Reference 2

